

UNATTENDED, CONTINUOUS PRINTING OPERATION COMBINED WITH THE VERY HIGHEST IMAGE QUALITY

STABLE PRODUCTION



NCU

Nozzle Check Unit automatically checks nozzles and cleans them if required.



operation.

NRS

Nozzle Recover automatically substitutes defective nozzles giving



HEATERS

3-way intelligent Pre- and print-heaters optimise ink adhesion uninterrupted



INTELLIGENT

accelerate drying.



MAPS4

HIGH IMAGE QUALITY

Mimaki Advanced **Pass System**

utilises finely tuned frequencies to precisely shape and place individual ink drops.



WFC Waveform Control

000

VARIABLE DOT

enables the printer to print in 3 different dot sizes to create high quality images with smooth gradations.

MIMAKI JV 100-160 SPECIFICATIONS

| | | Mimaki JV100-160C (Cartridge model) | Mimaki JV100-160B (Bottle model) ^(*1) |
|-------------------------|-----------------|--|--|
| Print head | | On-demand piezo head (2 staggered printheads) | |
| Print resolution | | 360 dpi, 600 dpi, 720 dpi, 900 dpi, 1200 dpi | |
| Ink | Type / Colour*1 | SS21 (C, M, Y, K, Lc, Lm, Lk, Or) AS5 (C, M, Y, K, Lc, Lm, Lk, Or) BS4 (C, M, Y, K) | CS250 (C, M, Y, K) |
| | Package size | 600ml (except for SS21) / 2L ink pack(12) | 1L ink bottle |
| Maximum print width | | 1,610mm | |
| Media | Max. width | 1,620mm | |
| | Thickness | Up to 1mm | |
| | Roll diameter | Up to 250mm | |
| | Roll weight | Up to 45kg | |
| Interface | | USB2.0 / Ethernet 1000BASE-T | |
| Power supply | | 2x single-phase (AC 100~120V / 200~240V ± 10%, 50/60Hz ± 1Hz) | |
| Power consumption | | AC100V: 1.44kW x 2 / AC200V:1.92kW x 2 | |
| Safety standards | | VCCI class A, FCC Class A, CE Marking (EMC Directive, Machinery and Low Voltage Directiv CB Certification, RoHS, RCM, EAC | |
| Operational environment | | Temperature: 20-30°C / Humidity: 35-65% Rh (Non-condensing) | |
| Dimensions (W x D x H) | | 2,775 x 700 x 1,392mm | 2,775 x 700 x 1,475mm |
| Weight | | 166kg | 168kg |

- 1: JV100-160B model is only available in non-EU countries.
- *2: 600ml ink pack is supplied in a reusable eco-case. Optional Mimaki Bulk Ink System (MBIS3) is required for using 2L ink pack.

Supplies & Options

| Item code |
|--|
| 2L ink pack: SPC-0588x |
| 600ml ink pack: AS5-x-60 / 2L ink pack: AS5-x-2L |
| 600ml ink pack: BS4-x-60 / 2L ink pack: BS4-x-2L |
| 1L bottle: CS250-x-BA |
| SPC-0294 (220ml ink cartridge) |
| ML014-Z-BA (1L bottle) |
| OPT-J0364 (Eco-case, Mid cartridge, Tube - 8pcs/each) |
| OPT-J0351 and OPT-J0512 (both required for installation) |
| OPT- J0353 |
| OPT-J0355 |
| |

Specifications, designs and dimensions in this list may be subject to change without notice due to technical improvements or other modifications



Offered at an entry-level price, the JV100-160 delivers the best print performance at the lowest running costs compared to other solvent printers in the sign printing market. Mimaki's proven technology featured in this new printer advances ease of use, and with the possibility to load 8 different colours, high definition colour reproduction comes standard.

NEW DOT ADJUSTMENT SYSTEM (DAS)

Introducing Mimaki's easy-to-operate Dot Adjustment System (DAS), which automatically performs bi-directional and media feed adjustments. This eliminates the need for manual adjustments. saving time and improving overall productivity.

* DAS may not be compatible with some media such as coloured, transparent, and embossed substrates.



landing position



Overlap / black streaks (Insufficient paper feeding)



Gap / white streaks (Excessive paper feeding)

Available in 8 colours, including Light Black and Orange the AS5 ink significantly improves the colour gamut. covering approx. 94.8% of the PANTONE coated colour chart. The 8-colour configuration also allows you the lowest running costs in the market today. The AS5 ink is

CS250 ink (*1)

AS5 ink

Offered at a highly competitive price, even compared to that of third-party inks, the CS250 eco-solvent ink is delivered in 1L ink bottles to ensure longer print operation.





UNBEATABLE PRINT AND CUT WORKFLOW

Combine the JV100-160 with a Mimaki cutting plotter for unbeatable print and cut productivity. Mimaki's latest cutting plotters feature the new ID Cut function, which enables printer operators to contour cut multiple jobs with minimal intervention, even for jobs longer than 2 metres. Offering trouble-free, automatic cutting of consecutive jobs, the ID cut function saves time and reduces potential material waste.



HIGH PRODUCTIVITY





Correct drop landing position and paper feeding

ensures the highest print quality

LOWER YOUR RUNNING COSTS

All Mimaki JV100-160 compatible inks are all GREENGUARD GOLD certified. Products that are GREENGUARD GOLD certified meet the rigorous standards for low emission of volatile organic compounds (VOCs) and ensure that a product is acceptable for use in environments such as schools and healthcare facilities.

NEWLY DEVELOPED ECO-SOLVENT INKS

In addition to Mimaki's popular SS21 and BS4 inks, the JV100-160 features two new fast drying

Also available for the 600ml ink packs: reusable eco-cases, which will eliminate the disposal of plastic.

SUSTAINABLE CHOICES THAT



ADVANCED RIP SOFTWARE



The JV100-160 comes with Mimaki's user-friendly RIP software, Rasterlink 7, as standard, featuring:

- 1. New HARLEQUIN RIP core for more accurate handling of PDF files with shadows and transparencies.
- 2. Up to 25% faster processing of complex PDF files.
- 3. Variable data printing to easily create a series of prints with dynamic variations of texts and photos.
- 4. Improved user interface and screen efficiency.

CREATE: Outdoor and indoor signage | Banners | Vehicle wrapping | POS displays | Window graphics | Stickers & labels

Floor graphics | Posters | Canvas | Backlit signs | Wallpaper | Transfer material and much more...